



P.O. Box 711 | 543 Third Street, Suite B1 | Lake Oswego, OR 97034

TEL 503.636.8191 | FAX 503.635.6140 | TOLL FREE 1.800.824.5671 | www.oregonlumber.com

OREGON LUMBER COMPANY

Sustainable Custom Wood Flooring since 1962

1-800-824-5671

www.oregonlumber.com

WORTHWOOD SOLID END GRAIN WOOD FLOORING MATERIAL SPECIFICATIONS

SPECIES: Douglas Fir, Hemlock, Alder, Oak, or Mesquite

CONSTRUCTION: Kiln Dried (6-9%) solid wood blocks turned on end and double edge wired with a soft aluminum wire to form a flexible strip

APPLICATION: Commercial or Residential

FINISH: Supplied Unfinished or Prefinished

SURFACE TREATMENT: Woca oil, or Urethane- Bona Traffic, Naturale or equivalent

INSTALLATION: Glue down, Bostic Best or equivalent urethane adhesive

STRIP LENGTHS: 12" – 34"

WIDTH OPTIONS: 2 ³/₄", 3 ¹/₄", 3 ⁵/₈", 4 ⁵/₈"

THICKNESS: ³/₄", 1", 1 ¹/₂", 2", 2 ¹/₂"

EDGES: Chamfered 1/64" to accomplish tight fit on top

ENDS: Precision square cut

BACKS: Double grooved. Bottom edges beveled

Factory Sanded: 60 grit for site finishing

LEED CONTRIBUTION:

MR 4 – Pre consumer content

MR 5- Within 500 miles of Portland, OR

MR 7 – When FSC is specified

IEQ 4.4 –No added urea formaldehyde